

BL022000 Marine FC-W Engine Oil 4-Stroke Inboard 25W-40

Document version: November 29th 2017



Description

The marine 4T Inboard / Outboard Oil is a four stroke engine oil based on high quality base oils with special additives, Because of the excellent "shear stability" with a very strong anti-corrosion, oxidation and wear-ability, this four stroke oil is suitable for use in inboard engines as well in high speed and heavy duty engines such as outboard engines of Mercury. This engine oil meets the latest requirements set by the NMMA. The specific marine oil is not suitable for use in outboard exhaust aftertreatment systems and for use in cars.

According to the specifications of

Packing units

Mercruiser
Mercury
NMMA FC-W

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL022001	1 L	6	450
BL022005	5 L	4	112
BL022020	20 L	1	30
BL022060	60 L	1	12
BL022205	205 L	1	2
BL022999	1000 L	1	-
PBL022000	bulk	1	-

Page 1/2

Typical characteristics

TEST	VALUE	
SAE	25W-40	
Density at 15°C	0,892	kg/l
Kinematic viscosity at 40°C	151,9	mm²/s
Kinematic viscosity at 100°C	15,5	mm²/s
Viscosity index	104	
Flashpoint COC	244	°C
Pourpoint	-21	°C
Total Base number	7,7	mgKOH/g

Page 2/2